

# PFT ANTI-DUST UNIT pro

Dust-free – clean and health-friendly working

Usually the dust formation during loading with bags can not be prevented, but greatly reduced.

## TECHNICAL DATA

Part no.	00 53 97 16
Dimensions: W/L	725 mm / 665 mm
Opening dimension: W/L	330 mm / 400 mm
Weight of hood	16.1 kg
Weight of deflector, clampable	2.3 kg
Connection vacuum cleaner	Internal diameter 37 mm
Including	
Industrial vacuum cleaner, category M*	
Power input max. 1400 Watt	
Hopper volume with dust 25 litres	
Reduction efficiencies of filter system > 99.9 %	
Suitability for hazardous dust with limit values 3) > 0.1 mg/m <sup>3</sup>	
Supplementary set for industrial vacuum cleaner M consisting of: 1 x handle tube, 2 x suction tube, 1 x crevice nozzle, 1 x dust nozzle	

\* Source: EN 60335-2-69 and IEC 60335-2-69 Annex AA



# ADVANTAGES AT A GLANCE



- 1** Low construction height - Filling height increases by approx. 2 cm
- 2** Floating dust is captured by another controllable suction nozzle
- 3** Clampable deflector
- 4** Including mounting hooks for mixing tube
- 5** Simple assembly by clever PFT supports
- 6** Robust and integrated bag squeezer
- 7** Suitable for all G 4 models

ACCESSORIES	PART NO.
<ul style="list-style-type: none"> <li>■ Industrial vacuum cleaner, category M*</li> </ul>	00 24 80 60
<ul style="list-style-type: none"> <li>■ Supplementary set for industrial vacuum cleaner M consisting of: 1 x handle tube, 2 x suction tube, 1 x crevice nozzle, 1 x dust nozzle</li> </ul>	00 42 68 94
<ul style="list-style-type: none"> <li>■ Clampable deflector</li> </ul>	00 53 84 45
<ul style="list-style-type: none"> <li>■ Extension hopper anti-dust unit</li> </ul>	00 53 84 16



\* Source: EN 60335-2-69 and IEC 60335-2-69 Annex AA

## The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.eu](http://www.pft.eu)  
[www.youtube.com/knaufpften](http://www.youtube.com/knaufpften)

Download now! APP: PFT - Plastering Technology

## Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

[info@pft-iphofen.de](mailto:info@pft-iphofen.de) [www.pft.eu](http://www.pft.eu)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ANTI-DUST UNIT pro - GB/03.16/PFT