Information

No. 232/PFT
Date: April 2013

NEW



Water pressure booster pump PFT AV 1000

230 V-version **Part no. 00 22 67 15**
400 V-version **Part no. 00 22 67 13**

Functional description:

The PFT AV 1000 is a radially priming pressure booster pump. The drive is protected by a casing with a convenient handle.

Applications:

The pressure booster pump is switched on if the required minimum flow pressure of 2.5 bar is not available on site, or if the machine is supplied with water from a tank.

Advantages at a glance:

- high capacity
- casing made from stainless steel
- insensitive to impurities in the used water

Technical data

Power connection	230 V, 50 Hz, 1 phase 400 V, 50 Hz, 3 phases
Input power	0,6 kW
Protection	IP X4
Supply rate	max. 80 l/min
Conveying height	max. 50 m
Liquid temperature	max. +40° C
Operating pressure allowed	max. 8 bar
Total weight	8.5 kg

All rights and technical changes reserved. We provide guarantee as far as faultless and proper finishing of our machines is concerned. Figures given in relation to output, equipment and performance are based onexperience and can vary in case of changing circumstances. Furthermore, the instructions of the material/mortar manufacturers must be observed. Alterations, reprints and photomechanical reproductions, even inextracts, require the permission of Knauf PFT GmbH&Co.KG.©Copyright by Knauf PFT Iphofen. Printed in Germany

PFT – THE FLOW OF PRODUCTIVITY

Knauf PFT GmbH & Co. KG
P. O. Box 60 97343 Iphofen Germany
Phone +49 9323 31-760
Fax +49 9323 31-770
info@pft-iphofen.de
www.pft.eu