

PFT BOARDMASTER 2750

High quality drywall construction - easy, fast and efficient

The cutting table PFT BOARDMASTER 2750 for cutting, milling and drilling. With the milling aggregates moldings and folding elements can be created in nearly every form.



TECHNICAL DATA

Part no.	00 61 19 28
Processing dimensions: L/W/H	2,750 / 1,260 / 48 mm
Total weight	~ 188 kg
Connection details	3 kW
Undertable	steel panel galvanised, aluminium
Maximum number of aggregate	2
Milling device	1050 Watt
Sawing device for longitudinal sections	1530 Watt
Sawing device for cross sections	1530 Watt
Circular template infinitely variable	from 150 mm to 1200 mm



ADVANTAGES AT A GLANCE

		<ul style="list-style-type: none"> 1 Precision unit with a quick-changing system 2 Precise guide carriages with a precision guide system, rear Guide system, rear Recirculating ball bearing guides – round shaft Guide system, front Recirculating ball bearing guides, prism-type linear guides on high-precision ground surface 3 Dust-free – integrated suction 4 PFTstrong – patented system for edges with high mechanical stress bearing capacity 5 Direct measuring system, electronic display Y-axis and X-axis; electromagnetic locking as per the head pressure 6 Copying by using different templates 7 Large working surface up to 2,750 x 1,260 mm; almost all commercially plates are workable Quick – easy machine operation Pneumatic lifting system of the unit for the Z-axis
		
		
		

FIELDS OF APPLICATION

- Exakt cuts of numerous materials
- Auditing system
- Window frames
- Stuccowork, columns
- Fire Protection and various panels



ACCESSORIES	PART NO.
■ Laser PreView – with 4 lasers the processing centre of milling device is shown	00 41 92 42
■ V-Groove saw 90° for plate 13 mm	00 47 16 56
■ Milling device 1050 Watt with integrated suction channel, swivelled to establish a sharpening angle up to 145°	00 47 16 52
■ PFTstrong edge table, magnetic – for preparing flat edges	00 20 80 70



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.

 **Click. Discover. Experience.**
www.pft.eu
www.youtube.com/knaufpften

Download now! APP: PFT – Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline	+49 9323 31-1818
Phone	+49 9323 31-760
Fax	+49 9323 31-770
info@pft-iphofen.de www.pft.net	

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT BOARDMASTER 2750 – GB/01.18/PFT