
SK and SKP runner



SK-/SKP runner for partitions EN 14195

PRODUCT DATA			
CHARACTERISTIC		VALUE	UNIT
Fire	Reaction to fire	A1	Incombustible
Strength	Yield point	250	N/mm²
Contents	Hazardous contents	NPD	
Surface	Zinc	140	g/m²
Corrosion class		C1	
Measurements	Widths ± 0.5	45/70/95/120/145/160	mm
	Thickness	0.50	mm
	Length	±	+ 0 / - 3
	Other - see drawing	±	1 mm

Areas of use

Runner with or without polyethylene. Can be slotted in to each other. 87° angle between the flange and the body. The runners have a flange height of 55 mm. For non-bearing constructions in buildings with plasterboard according to EN 520 or reprocessed products according to EN 14190.


Profiles produced according to EN 14195.

Variants/sizes:

Runner SK(P) 45/70/95/120/145/160 mm

PROFILE DATA					
	t	h	A	Iy	Wy
Profile	**mm**	**mm**	**mm²**	**mm⁴**	**mm³**
SK(P) 45	0,50	45	40,6	1,35 x 10⁴	0,45 x 10³
SK(P) 70	0,50	70	52,1	3,55 x 10⁴	0,81 x 10³
SK(P) 95	0,50	95	61,0	7,01 x 10⁴	1,19 x 10³
SK(P)120	0,50	120	66,0	11,36 x 10⁴	1,47 x 10³
SK(P)145	0,50	145	70,9	17,10 x 10⁴	1,79 x 10³
SK(P)160	0,50	160	74,0	21,38 x 10⁴	2,01 x 10³

Steel quality: S250GD+Z140



Knauf A/S
Kløvermarksvej 6
DK-9500 Hobro

Tlf. (+45) 9657 3000
info@knauf.dk
www.knauf.dk