

FSK runner



FSK reinforcement runner

For high walls and extra reinforcement

Page: 1/1

03/2017

PRODUCT DATA

CHARACTERISTIC		VALUE	UNIT
Fire	Reaction to fire	A1	Incombustible
Strength	Yield point	250	N/mm ²
Surface	Zinc	275	g/m ²
Corrosion class		C2	
Measurements	Widths ± 0,5	45/70/95/120/145/160	mm
	Thickness	1,5	mm
	Length	± + 0 / - 3	
	Other - see drawing	± 1	mm

Areas of use

Runner for FR studs for partitions.

For telescopic solutions for very high walls or for walls where a high degree of stability is required.

Profiles produced according to EN 14195.

Variants/sizes:

Runner FSK 45/70/95/120/145/160 mm

PROFILE DATA

	t	h	A	iy	ly	Wy
Profile	mm	mm	mm ²	mm	mm ⁴	mm ³
FSK 45	1,5	45	185,7	22,3	9,27 x 10 ⁴	2,2 x 10 ³
FSK 70	1,5	70	222,1	29,6	19,50 x 10 ⁴	4,37 x 10 ³
FSK 95	1,5	95	258,5	37,9	37,06 x 10 ⁴	6,39 x 10 ³
FSK120	1,5	120	295,0	46,1	62,75 x 10 ⁴	8,81 x 10 ³
FSK145	1,5	145	331,5	54,3	97,63 x 10 ⁴	11,58 x 10 ³
FSK 160	1,5	160	353,4	59,1	123,46 x 10 ⁴	13,39 x 10 ³

Steel quality: S250GD+Z275

