

AQUAPANEL®

08/2016

AQUAPANEL® Indoor Joint Adhesive

for AQUAPANEL® Cement Board Indoor

Be certain,
choose AQUAPANEL®

AQUAPANEL®

Description

AQUAPANEL® Indoor Joint Adhesive is used for wall applications to bond individual AQUAPANEL® Cement Board Indoor panels.

There is no need for labour-intensive coating or inserting a joint strip.

Processing/application

Before applying the AQUAPANEL® Indoor Joint Adhesive, ensure that the edges are cleaned using a wet brush. This ensures the best adhesion to the panel.

Apply a continuous linear bead of AQUAPANEL® Indoor Joint Adhesive to the clean edge of the already-fixed AQUAPANEL® Cement Board Indoor. This must be done before the next panel is placed. Additional filling of the joint is not allowed.

Place the next board onto the substructure and press against the joint adhesive (joint width approx. 1 mm). Ensure that the panels are correctly aligned horizontally and vertically and screw the board into place.

After 12 hours the adhesive is hardened to enable the next following working steps. Remove the excess joint adhesive using a scraper.

Material coverage

approx. 60 ml/m^2 (30 ml/m joint)

Cartridge contents sufficient for approx. 5.5 m^2

Technical data

Description	1K PVAc-adhesive
Density	1.5 g/ml
Moisture resistance	D3 following EN 204
Open time	8 – 10 minutes
Further processing	after 12 hours (at 20 °C/65 % rel. air humidity)
Final strength	after 7 days

Working time

Approx. 15 minutes/m^2 (incl. screws)

Working temperature/climate

The material, ambient and background temperature must not fall below +10 °C.

Working safety

This product is not classified as a hazardous product. Please find more information in the material safety data sheet.

Method of delivery/storage

- 310 ml/cartridge
- Store in a dry, cool and frost-free area
- Unopened storage life approx. 18 months

Item codes: 103389

AQUAPANEL®

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned.

www.AQUAPANEL.com
aquapanel.info@knauf.com

AQUAPANEL® is a registered trademark.

Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany

© 2016 EN-08/16

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany.