

PFT SILOMAT trans plus 100

The compact and transport-friendly conveying unit


The SILOMAT trans plus conveys dry mortar in a fully automatic and dust-free procedure. With very little effort the machine can be established and transported. Handling is considerably simplified by the numerous assistants, such as integrated crane transport eyes or fold-out carrying handles.

TECHNICAL DATA

Part no.	00 12 43 65
Conveying distance	100 m
Conveying output	20 kg/min
Motor	400 V, 3 Ph, 50 Hz
Compressor	Capacity: 5.5 kW Max. Pressure: 2.5 bar Air flow: 100 Nm ³ /h
Conveying pot content	55 litre
Dimensions: L/B/H	1,100/635/720 mm
Weight	~ 275 kg

Kindly note:

Conveying distance depends on the used materials.



ADVANTAGES AT A GLANCE

- 1** Fluidiser: Boosts and ensures the material flow; the vessel is nearly completely emptied
 - Maintenance-free
 - Resistant to humidity
 - Can be retrofitted
 - Performance increase by up to 30 %
- 2** Compressor is a dry running; no oil change needed
- 3** Rotary compressor: as rollable and portable execution available
- 4** Crane transport eyes and fold-out carrying handles
 - Suitable for container/silo discharge flange Ø 250 mm
 - Shut-off valve with actuator and handwheel
 - Easily replaceable seals
 - Bypass: manually controllable for stiff materials and longer delivery reaches
 - Long machine running times with a high level of operational reliability
 - Easy replacement of wear parts – also on site

FIELDS OF APPLICATION		ACCESSORIES / VERSIONS	PART NO.
<ul style="list-style-type: none"> ■ Gypsum-lime plaster ■ Cement render ■ Lime plaster ■ Masonry mortar ■ Machine-applied gypsum plaster 	<ul style="list-style-type: none"> ■ Bulk material ■ Aggregate ■ Ingredients 	<ul style="list-style-type: none"> ■ Conveying hose first equipment DN45 - 73.3 m 3x Rubber hose DN45 - 20 m C-coupling 1x Rubber hose DN45 - 13.3 m C-coupling 1x Hook fastener for hose ■ Injection hood, foldable for G 4 ■ Filling hopper for bagged material ■ Extension cable 5 x 4 mm², RED 5-32 A - 25 m ■ SILOMAT trans plus 100, rollable 	<ul style="list-style-type: none"> 00 47 34 24 00 42 06 64 20 71 60 00 20 42 39 20 00 12 43 66

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SILOMAT trans plus 100 - EN/06.19/PFT