



## PFT Mixing tube with double mixing zone for PFT G 4/PFT G 5

Part no. 0008 03 27

### Functional principle:

Dry mortar is mixed with water in the mixing zone to a pumpable mortar. After that it is pumped away. Thanks to the extension of the mixing tube the mixing time doubles and improves the mix.



### Advantages at a glance:

- ▶ 100 % longer mixing time
- ▶ Higher mixing intensity
- ▶ Compared to the standard equipment a mixing volume extension of 180 % is reached
- ▶ Changeable as complete unit consisting of:
  - Mixing tube extended
  - Pressure flange cpl.
  - Set of tie rods for 200 mm pump (type D 6 -2)
  - Stator TWISTER D 6-2
  - Rotor D 6-2 T
  - Cleaning shaft extended
  - Mixing shaft extended
- ▶ Easy assembly, i. e. only the motor unit has to be moved
- ▶ Due to an intensive pre-mixing the wearing time of the pump improves

Weight: 33 kg

WIR SORGEN FÜR DEN FLUSS DER DINGE



Knauf PFT GmbH & Co. KG  
Postfach 60 97343 Iphofen Deutschland  
Telefon +49 9323 31-760  
Telefax +49 9323 31-770  
E-Mail [info@pft-iphofen.de](mailto:info@pft-iphofen.de)  
Internet [www.pft.de](http://www.pft.de)