

PFT SWING M FC-230V

The smallest conveying pump ideal for pasty filling plasters

The PFT SWING M have an electrical infinitely adjustable 1.5 kW direct drive. You can pump, press and spray liquid, pumpable and solvent-free materials (in buckets) up to a grain size of 3 mm.



TECHNICAL DATA

Part no.	00 15 19 92
Maximum working pressure	20 bar
Maximum conveying capacity	continuously variable conveying output of 9 l/min
Maximum conveying distance	up to 20 m
Motor	230 V, 1 Ph, 50 Hz, 1.5 kW, 10 - 204 rpm
Hopper content	38 litre
Rotor/Stator	C 4-2
Material outflow	DN25 male part
Material hopper	plastic
Wheels	2 castors, 2 wheels
Dimensions: L/W/H	1,100/460/500 mm
Filling height	500 mm
Total weight	~ 70 kg

Kindly note:
Conveying distance depends on the used materials.



	
230 V	1,5 kW
	
1 Ph	9 l/min

ADVANTAGES AT A GLANCE



- 1** Pump performance continuously adjustable via potentiometer
- Plastic material hopper – easy cleaning
- Cleaning port in the material hopper
- Variable conveying output through pump change (B or C pump)
- Small, light, handy and compact
- Powerful and reliable operation via standard power socket
- Fast cleaning and maintenance
- Transport is possible in any estate car
- Fits easily under each mixer
- Optional: electrical remote control

FIELDS OF APPLICATION

- Lime-cement render < 3 mm
- Adhesive and reinforcement mortar
- Fine filler
- Finishing coat
- Dispersion paint
- Primer Betokontakt

ACCESSORIES

- Extension cable 3 x 2,5 mm², BLU 2-16 A – 25 m
- Remote control cable with switch – 25 m
- Cover for SWING M
- Water hose Geka / Geka DN12 – 5 m
- Nozzle Geka DN19

PART NO.

20 42 34 00
 20 45 69 29
 00 15 93 23
 20 21 11 00
 20 21 57 00

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpften

Download now! APP: PFT – Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SWING M FC-230V – EN/09.19/PFT