

# PFT MULTIMIX 140 plus

## The multi-component mixer for the professional


The powerful batch mixer, which is particularly suitable for special mixtures of different components. Strong mixing arms save time for a homogeneous mortar mixture. Clever in the system - the mixed material is delivered to a PFT conveying pump, which transports the pumpable material directly to the processing place.



### TECHNICAL DATA

Part no.	00 25 16 36
Motor	400 V, 3 Ph, 50 Hz, 2.2 kW, 56' rpm
Mixing capacity	80 litres/batch
Hopper content	max. 140 litres
Mixing hopper	Steel
Operation and control	Start/Stop
Grain size	max. 8 mm
Water connection	Geka DN19 - 2.5 bar pressure
Filling height	1,120 - 1,400 mm
Outlet height	400 - 720 mm, adjustable
Dimensions: L/W/H	1,000 / 1,030 / 1,120 mm
Weight	~148 kg

**Kindly note:**  
All details depends on the used materials.



## ADVANTAGES AT A GLANCE



- Easy handling
- Minimal maintenance and cleaning effort
- Self-cleaning mortar outlet
- Phase converter in main switch
- Opposite agitators
- Turbo mixing system
- Robust design for construction site
- Height adjustable
- Fits easily over a conveying pump such as the ZP 3 or SWING

### FIELDS OF APPLICATION

- Concrete restoration
- Powder adhesive
- PCC- and SPCC-mortar
- Mineral plaster
- Fine-grained concrete
- Acoustic plaster
- Epoxy resins
- Screed
- Artificial resin plaster
- Masonry
- Granulates
- Loam plaster
- Furnace construction

### ACCESSORIES

- Extension cable 5 x 4 mm<sup>2</sup>, RED 5-16 A - 25 m
- Water pump AV300 230 V, 1 Ph, 50 Hz, 0.6 kW
- Suction strainer with filter screen
- Water hose Geka/Geka DN12 - 5 m
- Spray nozzle Geka DN19

### PART NO.

20 42 33 60  
00 49 36 86  
00 13 66 19  
20 21 11 00  
20 21 57 00

### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpften](http://www.youtube.com/knaufpften)

Download now! APP: PFT - Plastering Technology

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT MULTIMIX 140 plus - EN/02.20/PFT