

PFT SILOMAT trans plus bag

Perfect for job sites without space for silos


No place on the job site? With the SILOMAT trans plus bag large amounts of material can be transported without an silo. All with one - the compact conveying unit for material in bags and also in silos.



TECHNICAL DATA

| | |
|-----------------------|---|
| Part no. | 00 16 99 52 |
| Conveying distance | 140 m |
| Conveying output | 20 kg/min |
| Motor | 400 V, 3 Ph, 50 Hz |
| Compressor | Capacity: 7.5 kW Max. Pressure: 2.5 bar Air flow: 140 Nm³/h |
| Conveying pot content | 60 litre |
| Dimensions: L/W/H | 1,100/635/720 mm |
| Weight | ~ 294 kg |

Kindly note:
Conveying distance depends on the used materials.



ADVANTAGES AT A GLANCE










- 1** Fluidiser: Boosts and ensures the material flow; the vessel is nearly completely emptied
 - Maintenance-free
 - Resistant to humidity
 - Can be retrofitted
 - Performance increase by up to 30 %
- 2** Compressor is a dry running; no oil change needed
- 3** Crane transport eyes and fold-out carrying handles
- 4** Suitable for container/silo discharge flange Ø 250 mm
- 5** Easily replaceable seals
- 6** Socket for lift truck
- 7** Socket for fork lift
- Bypass:** manually controllable for stiff materials and longer delivery reaches
- Long machine running times** with a high level of operational reliability
- Easy replacement of wear parts** – also on site
- Shut-off valve with actuator and handwheel**
- Rotary compressor:** as rollable and portable execution available

| FIELDS OF APPLICATION | | ACCESSORIES | PART NO. |
|--|---|---|---|
| <ul style="list-style-type: none"> Gypsum-lime plaster Cement render Lime plaster Masonry mortar Machine-applied gypsum plaster | <ul style="list-style-type: none"> Bulk material Ingredients Powder material Lime cement plaster ... and many more | <ul style="list-style-type: none"> Conveying hose first equipment DN45 - 73.3 m 3x Rubber hose DN45 - 20 m C-coupling 1x Rubber hose DN45 - 13.3 m C-coupling 1x Hook fastener for hose Extension cable 5 x 4 mm², RED 5-32 A - 25 m Cover for conveying pot DUSTCATCHER G 4 complete Adaptor for silo connection | <ul style="list-style-type: none"> 00 47 34 24 20 42 39 20 00 20 12 67 00 53 97 16 00 19 50 80 |

The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net

www.youtube.com/knaufpften

Download now! APP: PFT – Plastering Technology

Knauf PFT GmbH & Co. KG
Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SILOMAT trans plus bag – EN/06.19/PFT