


PFT AV 1000 standalone

For constant water supply

Effective water pump in stainless steel design with high flow rate, pressure switch-off and idling protection. The water supply from a water tank is ensured fully automatically by the AV 1000 standalone.




- no dry running thanks to idle running protection
- automatic pressure switch-off at stopped machine
- high capacity
- stainless steel



TECHNICAL DATA

Part no.	00 49 36 86	00 52 73 99
Power connection	230 V, 1 phase, 50 Hz	230 V, 1 phase, 60 Hz
Drive	0.6 kW	0.6 kW
Protection	IP 44	IP 44
Conveying capacity	max. 3 m ³ /h, 50 l/min at 2 bar max. 2.6 m ³ /h, 44 l/min	
Conveying height	max. 40 m	max. 40 m
Suction height	up to 9 m [*]	up to 9 m [*]
Liquid temperature max.	+ 40°C	+ 40°C
Operating pressure allowed max.	5.5 bar	5.5 bar
Dimensions: L/W/H	400 / 270 / 590 mm	400 / 270 / 590 mm
Weight	~ 13.5 kg	~ 13.5 kg

***Please consider:**
Please consider the operating instruction included at initial operation.

FIELDS OF APPLICATION

Guarantee of constant water supply to PFT machine technology.
Use, for example, in combination with a water barrel or in the event of pressure fluctuations in the water pipe.
The flow pressure of 2.5 bar at running machine is guaranteed on building sites while sucking from a water tank.

ACCESSORIES

ACCESSORIES	PART NO.
■ Suction strainer, stainless steel	00 13 66 20
■ Suction strainer with filter screen	00 13 66 19

