

# PFT HM 24

## The clever bagged material and silo mixer

The allrounder among the continuous mixers. It is especially suitable for the application of adhesive mortars. The PFT HM 24 is characterized by its easy handling.




### TECHNICAL DATA

Part no.	00 02 03 57
Mixing capacity	max. 25 - 50 litre / min
Motor	400 V, 3 Ph, 50 Hz, 3 kW, 280 rpm
Mixing tube	Rubber mixing tube
Grain size	max. 6 mm
Water connection	DN12 Geka - 2.5 bar at running machine
Wheels	2 wheels
Operation and control	Start/Stop
Pedestal	fix
Hopper content	110 litre
Dimensions: L/W/H	1,870/670/970 mm
Filling height	970 mm
Output height	650 mm
Weight	~ 110 kg

#### Kindly note:

Mixing output capacity depends on the used materials.



**PFT – ALWAYS AT YOUR SITE**

## ADVANTAGES AT A GLANCE



- 1** Removeable mortar outlet
- 2** Water manifold with pressure reducer
- 3** Perfect interaction between screw mixer and conveying pump
- 4** Silo and container transfer is possible by an delivery hood (Part no. 20 60 05 00)
- Minimal maintenance and cleaning overhead
- Easy to transport
- Phase inverter in connection plug
- Rubber mixing tube: no caking of the materials
- Easy operation
- Constant mixing quality

### FIELDS OF APPLICATION

- Masonry mortar
- Light masonry mortar
- Reinforcing mortar
- Scratch coat
- Cement plaster
- Insulation plaster
- Screed mortar
- Levelling compound
- Adhesive mortar
- Grater mortar
- Restoration plaster
- Tiling and jointing mortar
- High-grade plaster

### ACCESSORIES

- Extension cable 5 x 2.5 mm<sup>2</sup>, RED 5-16 A - 50 m
- Water hose Geka|Geka DN19 - 40 m
- Spraying cap DN19 Geka
- Material extension hopper - 142 Liter
- Cover for material hopper
- Mixing shaft HM 24, earth-moist materials

### PART NO.

- 20 42 33 50
- 20 21 21 00
- 20 21 57 00
- 00 45 34 69
- 00 20 12 67
- 00 51 30 92

### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpften](http://www.youtube.com/knaufpften)

Download now! APP: PFT - Plastering Technology

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT HM 24 - EN/09.19/PFT