



Agitator PFT ROTOMIX disc for floor knifing fillers

Part no. 00 20 93 75

Functional description:

The disc inside the agitator PFT ROTOMIX is driven via the tang on the Rotor. A second disc inside the housing completes the mixing system and the two discs create a shearing of the material. By that, any lumps are completely dispersed and the material is intensively mixed.

Field of applications:

for many materials such as:

- ▶ levelling compounds
- ▶ self-levelling screeds

Advantages at a glance:

Material adjectives are improved by the after mixing process which helps to achieve utmost material quality. Lumps can be avoided.

PFT ROTOMIX disc consisting of:

- agitator housing
- agitator cover for D-pumps
- disc
- coupling 1", 35 male part, 1 1/4", IG
- tie rods (2 pieces)

Weight: 11.6 kg

Accessories required:

Pump unit D8-1.5, approx. 30 l/min

Rotor D8-1.5 with tang, Part no. 20 11 47 20

Stator TWISTER D8-1.5 PIN, Part no. 00 01 09 05

Mortar pressure gauge 35 mm cpl., Part no. 00 10 22 28

PFT – THE FLOW OF PRODUCTIVITY



Knauf PFT GmbH & Co. KG
P.O. Box 60 97343 Iphofen Germany
Phone +49 9323 31-760
Fax +49 9323 31-770
info@pft-iphofen.de
www.pft.eu