



GIFAfloor pedestal adhesive EC 1

Adhesive for Knauf GIFAfloor pedestals

Product description

GIFAfloor pedestal adhesive EC 1 is a viscous adhesive for the installation of Knauf GIFAfloor pedestals.

Storage

Keep away from (strong) acids. Store closed, cool, dry and protected from the effects of weather. Shelf life at least 12 months.

Quality

The product is subject to continuous factory production control.

Properties and added value

- High adhesive power
- Optimised for Knauf GIFAfloor pedestals
- Does not pull threads
- Solvent free
- Very low emission, EMICODE EC 1^{PLUS}
For details see www.emicode.com



Adhesive for Knauf GIFAfloor pedestals

References to other documents

- F18.de Knauf GIFAfloor hollow floor
- F185.de Knauf GIFAfloor DB green raised access floor

Application

Application temperature / -climate

Process between +15 and +25 °C.

Application time

After 12 hours, the pedestals can be walked on.

Maximum strength is reached after 7 days.

Cleaning

Remove any fresh adhesive that has come out. Wash tools and brushes thoroughly with water immediately after use.

Product range

Description	Consumption	Packaging Unit	Article number	EAN
GIFAfloor pedestal adhesive EC 1	Approx. 1 foil tube / 40 pedestals	600 ml / foil tube	260231	4003982430489
	Approx. 8 m ² / foil tube			

Accessories

Description	Version	Packaging Unit	Article number	EAN
Knauf adhesive gun	For foil tubes with 600 ml	Piece	4657	4003982087270



Observe safety data sheet!
For safety data sheet see
pd.knauf.de



The App Knauf Infothek provides all the current information and documents from Knauf Gips KG at any time and in every location in a clear and comfortable way.
knauf.de/infothek

Knauf Direct

Technical Advisory Service:

▶ knauf-direkt@knauf.com

▶ www.knauf-integral.de

Knauf Integral KG Am Bahnhof 16, 74589 Satteldorf, Germany

All technical changes reserved. Only the current printed instructions are valid. The stated information represents current state-of-the-art Knauf technology. The entire state of approved engineering rules, appropriate standards, guidelines, and rules of craftsmanship are not included herewith. These and all application instructions have to be adhered to separately by the installer. Our warranty is expressly limited to our products in flawless condition. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas.

All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require our expressed permission.