



Tile adhesives

K521.lv

Technical data sheet

10/2023



K6

Fast-setting, flexible tile adhesive

Product description

Fast-setting, flexible, water and frost resistant, thin-layer, high-quality cement-based tile adhesive.

Composition

A mixture of dolomite and natural sand with portland and alumina cement, enriched with polyvinyl acetate polymer and additives to improve mass properties.

Type C2F

acc. to LVS EN 12004

Storage

6 months. Store in a dry, cool place on wooden pallets in unopened original packaging. Seal open bags hermetically and use as the first.

Quality

In accordance with the requirements of LVS EN 12004, a product type test has been carried out in a notified laboratory, constant control of the production process is ensured. The product is marked with the CE mark.

Features and added value

- Especially suitable for repair works
- Fast-setting
- Flexible
- Thermal resistance from -20 °C to +80 °C
- High initial adhesion
- Without shrinkage and tension
- Water resistant
- Frost resistant
- Load resistant
- Hydraulic curing
- Manual application
- For indoor and outdoor use

Fast-setting, flexible tile adhesive

Field of application

The thin-layer tile adhesive can be used for walls and floors, and can also be used for heated floors.

Suitable for:

- heavy-use, stable surfaces,
- areas that need to be used soon – stairs, corridors, sanitary premises.

Intended for:

- gluing ceramic tiles and slabs,
- gluing degreased, opaque natural stone slabs.

For indoor and outdoor use.

Application

Substrate and pretreatment

The base should be smooth, hard, unfrozen, free of any dust, paint and oil residues. If surfaces are plastered in tiles, the plaster should be applied at least 10 mm thick, in one layer and not smoothed.

The maximum allowable humidity of the substrates

Substrate	Max. moisture content
Cement floor covering	4 %
Cement floor covering with heating	2 %
Gypsum anhydrite floor	0.5 %

Preparation

Highly absorbent and absorbent bases should be primed with Knauf Spezialhaftgrund (diluted 1:2 with water) or Knauf Tiefengrund.

Non-absorbent surfaces – polished concrete, terrazzo, etc. primed with Knauf Spezialhaftgrund (undiluted).

Knauf Flächendicht or Knauf Flex-Dicht waterproofing should be applied to surfaces where the influence of moisture is expected.

Tile only after the primer has completely dried.

Mixing

Mix the content of one bag (25 kg) with 5.5-6 l of clean, cold water, mix by hand or with a slowly rotating mixer until a homogeneous mass without lumps forms, allow to swell for 5 min and mix again. Adjust the consistency by adding powder or water to the mixture.

Application

First, the mixed adhesive should be applied with a trowel or ladle to the entire prepared surface in the appropriate layer thickness. Then, holding the trowel at a 90° angle, comb with a suitable notched trowel (the sizes of the notches are specified in the Consumption Table).

The tiles should be placed in a layer of adhesive and firmly pressed with a slight twisting motion.

If a film forms (check with your finger), the adhesive should be reapplied. The time of laying and adjustment depends on the absorbent capacity of the base and tiles, as well as the ambient temperature.

In outdoor work and on the floor, the tile adhesive should provide adhesion over the entire surface of the tile.

In such cases, the tile adhesive should be applied both on the tile and on the base.

Use only clean tools and vessels!

Grouting

Grouting can be done only after the adhesive has cured – after 4 hours.

Tiling of heated floors

The underfloor heating should be commissioned before tiling.

Heated floor systems should be switched on at maximum temperature for at least 24 hours before starting tiling. It should be switched off and cooled before starting work. Full heating may be switched on no sooner than 28 days after tiling.

Temperature/climate

Air and base temperature during development and drying should be between +5 °C and +25 °C.

Protect newly laid tiles from drafts, direct sunlight and rain.

The technical data of the development are defined under the conditions, if the temperature of air and the base is +23 °C and relative air humidity is 50 % during curing.

Drying

The drying time depends on the absorbent capacity of the base, air temperature and humidity in the room.

Cleaning

Wash tools with water immediately after use.

Notes	Attention!
	The larger the tiles and the lower their water absorption capacity, the slower the adhesive dries.
	Spots smeared with adhesive should be cleaned immediately.
	The instructions and recommendations of the tile manufacturer should also be taken into account.
	Do not add other materials to Knauf K6, as they can significantly change the properties of the product.

Other instructions

Soluble hexavalent chromium Cr (VI) ion content < 0.0002 %.

When tiling less loaded wall surfaces – around 70 % adhesive coverage is allowed.

For outdoor works and heavily loaded surfaces, the combined method should be used (adhesive is applied both to the base and to the tiles); achieving up to 100 % adhesive contact with the base. This method should also be used when laying very weak (< 0.5 %) water absorbing tiles.

If the material has got into the eyes, rinse them with plenty of water and seek medical help.

This technical datasheet defines the scope of use of the material and the recommended work to be carried out, but it cannot replace the skill of the worker. In addition to these recommendations, the work should be carried out in accordance with the requirements of the construction work. The manufacturer guarantees the quality of the product, but this has no influence on the way and conditions of its application. In case of doubt, a trial application should be carried out.

This technical datasheet supersedes previous editions of technical datasheets.

Work safety and waste collection

Waste identification class:

170904

(see the material Safety Data Sheet).

Technical data

Designation	Unit / Standart	Value / Size
Type	acc. to LVS EN 12004	C2F
Layer thickness	mm	2-8
Working time	min	25
Tiling time*	min	15
Tile adjustment time*	min	8
The time of grouting for the wall	h	4
The time of grouting for the floor	h	4
Walking on the surface	h	4
The surface can be fully loaded after	days	7
Adhesion – to concrete	N/mm ²	> 1.0
Initial adhesion	N/mm ²	> 0.5
Reaction to fire	acc. to LVS EN 13501-1	A1 / A1 _f
Applying temperature	°C	+5 to +25
Thermal resistance	°C	-20 to +80

* The time depends on the type of tiles and the ambient temperature

Material requirement / Consumption

Tile size cm	Trowel notch size mm	Consumption* kg/m ²
up to 10	4	1.9
up to 15	6	2.4
up to 25	8	3.1
up to 30	10	3.9
30 and more	12	4.0

* Adhesive consumption is not determined by the size of the tiles, but by the thickness of the adhesive layer, which depends on the size of the trowel's notches

Product range

Product	Packaging	Material number	EAN
K6	25 kg	00289017	4750614006269
K6	5 kg	00527970	4750614006696

Knauf info center:

► Tel. +371 67 032 999

► info@knauf.lv

► www.knauf.lv

Manufacturer: SIA Knauf, Daugavas Street 4, Saurieši, Stopiņi Parish, Ropaži District, LV-2118, Latvia.

SIA Knauf reserves the right to make technical changes. The warranty only applies to the flawless properties of the material. Indicators of material consumption, quantity and performance are quantities obtained as a result of experience, which cannot be applied to each individual case literally. The given values do not exempt the buyer/seller from checking the validity of the product for the respective application. The publication is protected by copyright. Changes, reproductions and copies, including parts thereof, are possible only with the permission of SIA Knauf.

The building physical, static and technical properties of the Knauf system are fully guaranteed only if the components of the Knauf system or products specifically recommended by Knauf are used.