

# PFT BOLERO FC-230V

Perfect for material which is roughed up intensely

The clever solution allows an endless mixing. Material with a long mixing time can be processed in perfect quality.



## TECHNICAL DATA

Part no.	00 24 53 37
Working pressure	max. 20 bar
Conveying capacity	up to 9 litre / min
Conveying distance	up to 30 m
Motor	230 V, 1 Ph, 50 Hz, 2.2 kW, 181 rpm
Connection cable	BLU 3-16 A   BLU 2-16 A - 25 m
Hopper content	68 litre
Rotor/Stator	D 4-2
Material outflow	DN35 female part
Agitator	BOLERO centro
Dimensions: L/W/H	800/700/1,500 mm
Filling height	950 mm
Weight	~ 112 kg

**Kindly note:**  
Conveying distance depends on the used materials.



# ADVANTAGES AT A GLANCE



- Combination of mixing, pumping and spraying pump with clockwise and anti-clockwise operation
- Stipulated mixing and mortar source times can be precisely adhered
- Mixing errors are virtually eliminated
- Mortar pressure gauge integrated
- Big wheels matched to specific site conditions
- Cleaning port on material hopper
- Flexible mixing intensity
- Frequency converter (FC) for infinitely variable speed control and torque amplification
- Powerful and reliable operation via standard power socket

## FIELDS OF APPLICATION

- Grouting, reinforcing and adhesive mortars
- Fire protection mortar
- Mortar of various components
- Bentonite
- Structure and acoustic plaster
- Levelling compound

## ACCESSORIES

- Extension cable 3 x 2,5 mm<sup>2</sup>, BLU 3-16 A | BLU 2-16 A - 25 m
- ZARGOMAT pro DN25-360°
- JETSET pro DN25 Ewo
- Spraying set Finishing coats
- RONDO DN25 - 15 m
- Air hose DN12 Ewo | Geka - 15 m

## PART NO.

- 20 42 34 20
- 00 42 00 58
- 00 41 89 75
- 00 23 21 06
- 00 02 11 01
- 20 21 16 01

## The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpft](http://www.youtube.com/knaufpft)

Download now! APP: PFT - Plastering Technology

## Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT BOLERO FC-230V - EN/04.19/PFT