

# PFT RITMO M FC-230V powercoat


## The innovation in mixing and spraying technology

The proven PFT RITMO with the revolutionary agitator made of stainless steel/rubber which, for the first time, enables the machine crushing lumps to thereby produce a homogenous sprayable thin-wall plaster.

### TECHNICAL DATA

Part no.	00 09 06 38
Working pressure	max. 25 bar
Conveying capacity	continuously adjustable at 3 litres/min
Conveying distance	up to 20 m
Motor	230 V, 1 Ph, 50 Hz, 1.5 kW, 140 - 575 rpm
Hopper content	45 litres
Connection cable	3 x 2.5 mm <sup>2</sup> BLU 3-16 A   BLU 2-16 A - 25 m
Rotor/Stator	A 2-2,5 L
Spraying gun	powercoat DN13 VA4 1500 Ewo, hand grip
Material outflow	DN13 female part
Material hose	RONDO DN13 - 15 m
Adapter coupling	DN19 male part   Geka
Water flow meter	31.5 - 315 l/h
Dimensions: L/W/H	750 / 600 / 1,430 mm
Filling height	900 mm
Weight	~ 100 kg

**Kindly note:**  
All details depends on the used materials.



## ADVANTAGES AT A GLANCE



- 1** Suitable for buckets or bagged material
- 2** Rubber mixing zone, for easy cleaning, with replaceable flange for A and B pump
- 3** Flexible mixing intensity thanks to two water inlets
- 4** Fits in every car sedan
- Easy handling during commissioning, retrofitting, maintenance and cleaning
- Easy dismantlable into three modules
- Ready for remote control cable
- Conical mixing tube for optimum material flow
- Can be used at all construction sites with 230 V alternating current

### FIELDS OF APPLICATION

- Full-surface filling of drywall and concrete walls
- Filling of primed raw ceilings
- Finish filling of walls
- Filling as preparation for high-quality painting
- Surface quality Q3 and Q4

### ACCESSORIES

- Spraying gun powercoat DN13 VA4 750-45° Ewo
- Pressure tester 0 - 100 bar DN13 male part
- COMP P-400 230 V, 1 Ph, 50 Hz, 2.2 kW
- Consistency checking tube 13 male part

### PART NO.

00 09 80 71  
00 09 90 61  
00 23 31 74  
00 09 90 57



### The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

[www.pft.net](http://www.pft.net)  
[www.youtube.com/knaufpften](http://www.youtube.com/knaufpften)

Download now! APP: PFT – Plastering Technology

### Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net [www.pft.net](http://www.pft.net)

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

RITMO powercoat A 2-2,5 L – EN/03.19/PFT