



Finitura Fine Finisher

Advantages

Ready to use extra smooth fine finisher:

- Provides smooth finished surface
- Specially formulated to go over plaster
- Low paint absorption
- Economical

Application

Sheetrock® Finitura is specially formulated for treatment of gypsum plaster, but can be applied to different surfaces with excellent result, as follows:

- * Gypsum board
- * Concrete
- * Masonry

The material can be applied both manually or via airless machine with minimum debit of 4 liters/minute.

Layer of max 3 mm is recommended when applied by hand. When sprayed, the material can be diluted - up to 1 liter of water per 20 kg. Recommended nozzle size 531.

For best results, 2 layers of application is recommended especially when covering plaster.

Can be applied as finishing layer after skim coating with Sheetrock All Purpose.

After application the surface can be sanded, if required. Recommended grid paper № 280 or higher.

The temperature of the air and surfaces during application should be min 13° C, max 35° C.

Description

Ready mix finishing compound for interior use. Sheetrock® Finitura is a smooth fine finisher for interior use. Provides excellent workability with good open time and ensures extra smooth surface with strong bonding onto gypsum board, plaster, concrete, and masonry. The low paint absorption makes Finitura an economic solution, especially when designer high-end paints are applied. Surface can be sanded once dry to remove any imperfection.

Finitura

Fine Finisher

Advantages

Ready-mixed formula - no waste. After application rest of the material can be stored in a closed pail

- * Easy to apply
- * Extra smooth finished surface
- * Low paint absorption - reduces paint consumption

Consumption

Depends on the type and quality on substrate surface!
indicative consumption on gypsum plaster:
1 kg/sqm on gypsum board: 0.800 kg/sqm.

Product Data

Fine Finisher, vinyl based formula.
Suitable for both hand and machine application.

Packaging

25 kg pail
6 kg pail
20 kg bag

Storage

Store Finitura closed in dry and fresh spaces. Storing temperature:

5°<>30°.

Rotate stock on first-in, first out basis.

Max storing time:9 months. Protect from freezing!

Color

White



SHEETROCK®

KNAUF GYPSOPIIA A.B.E.E.

10 Euripidou Str., GR 176 74 Kallithea

Tel.: 0030 210 9310567/9, Fax: 0030 210 9310568, E-mail: knauf@knauf.gr

Werk: Stanos, GR 305 00 Amphiloehia

Tel.: 0030 26420 29100, Fax: 0030 26420 29112, 29115