

PFT CUTMASTER 1100/310


The hot wires for rational application of insulation panels

Quickly. Comfortably. Accurate to the millimetre. The PFT CUTMASTER is reduced in the construction to the bare essentials. But for the fast, clean and precise workflow the CUTMASTER has everything.





















TECHNICAL DATA

Part no.	00 25 66 38
Cutting height	1,110 mm
Cutting depth on 90 degree	310 mm
Mitre cuts laterally	Cutting bows on the right and left side, tilting to 45° angle
Cutting bows	Made by aluminium with integrates push button
Stand base	Folding feet enable to work on the scaffold, freestanding working with third removeable feet
Aluminium support angle lenght: left/right	980 / 420 mm - including longitudinal scale
Base plae	Multi-layer board coated - water resistant
Transformer	Primary 230 V, 50 Hz Secondary 28 V, power 150 VA - protection against splashing water
Twice fuse protection transformer - safe and powerful	High cutting speed and a short heating time
Dimension for transport: D/W/H	190 / 700 / 1,350 mm
Total weight	~ 17 kg



PFT – ALWAYS AT YOUR SITE

ADVANTAGES AT A GLANCE

1 	2 	4 	1 PUR spiral cable with anti-kink device – no crossing
3 	5 	6 	2 Locking the cutting depth with scale length
8 	9 	10 	3 4 Straightedges, recessed and scrub resistant
11 	7 	11 	4 Safe and powerful – twice fuse protection transformer
10 	8 	9 	5 Angular adjustments, right and left – adjust and fix the cutting bow from 0 to 45 degree
7 	6 	11 	6 Transport by crane with hooks and eyelets
6	5	4	7 Transport in an estate car
5	4	3	8 Even when the CUTMASTER folded it stands on the feet – no scratching
4	3	2	9 Depth stop attachment screw – adjustable depth stop stops the cutting bow
3	2	1	10 Aluminium supporting bow, right and left – adjust and lock variable from 0 to 90 degree
2	1	11	11 Replacement cutting wire, 10 m at the back
1	11	10	Welded robust cutting bow aluminium

FIELDS OF APPLICATION

- Heat insulation of the complete interior and exterior sector
- Perfect insulation of the facade, even in difficult places, e. g. under the eaves or window ledges



ACCESSORIES

- Support for scaffold PFT CUTMASTER Holding device allows a quick attachment of the polystyrene cutter on the scaffold
- Transport case
- PFT CUTMASTER 1100/310 – 110V

PART NO.

00 27 13 58
00 40 20 69
00 42 49 06



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Download now! APP: PFT – Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT CUTMASTER 1100/310 – EN/03.20/PFT