

PFT ZP 3 M FC-230V

The small solution for big challenges

The smallest member of the ZP 3 conveying pump family is characterized by a compact design, a low weight and an optimum production of almost all construction mixtures.




TECHNICAL DATA

Part no.	00 54 25 26
Working pressure	max. 20 bar
Conveying capacity	continuously adjustable 8 - 33 litre/min
Conveying distance	up to 60 m
Motor	230 V, 1 Ph, 50 Hz, 4 kW, 120 rpm
Hopper content	85 litre
Spraying gun	DN35 S16 male part Geka
Air compressor	COMP P-200, 230 V, 1 Ph, 50 Hz, 0.5 kW - 200 l/min
Material hose	RONDO DN35 - 10 m
Water/air hose	DN12 Ewo male part Geka - 11 m
Rotor / Stator	RENDER STAR
Material outflow	DN35 female part
Filling height	640 mm
Dimensions: L/W/H	1,800/600/670 mm
Weight	~197 kg

Kindly note:

Conveying distance depends on the used materials.



PFT – ALWAYS AT YOUR SITE

ADVANTAGES AT A GLANCE



- 1** Wide base tyres - good mobility
 - 2** Integrated pressure control for compressor
 - 3** Folded protection grille with switch-off function
 - 4** Two handles on the material hopper
 - 5** Handle at the pressure flange
 - 6** Integrated compressor console and hook
 - 7** Optionally: Vibrator screen
 - 8** Better cleaning of the machine and the cleaning opening by C-coupling - material hopper runs empty
- Machine shutdown via remote switch
 - Flow-optimized material hopper

FIELDS OF APPLICATION

- Jobsite mixture
- Screed mortar
- Cement plaster

ACCESSORIES / VERSIONS

- Extension cable 3 x 2.5 mm²
BLU 2-16 A - 25 m
- Vibrator screen 230 V
- ZP 3 M FC-230V
- ZP 3 M pole switchable
- ZP 3 M FC-400V

PART NO.

- 20 42 34 00
- 00 54 11 74
- 00 54 25 26
- 00 54 25 28
- 00 54 25 27



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpft

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ZP 3 M FC-230 V - EN/06.19/PFT