

PFT SWING L


Powerful, universal applicable pump

The powerful drive of 5.5 kW processes pasty materials, such as glue mortar or finishing coat up to a maximum grain size of 8 mm. The conveying pump, which achieves its compact dimensions, large conveying capacity and height. Transport is in any estate car without dismantling possible.

TECHNICAL DATA

Part no.	00 19 78 29
Working pressure	max. 30 bar
Conveying capacity	15,4 litres / min
Conveying distance	up to 50 m
Motor	400 V, 3 Ph, 50 Hz, 5.5 kW, 280 rpm
Hopper content	76 litres
Rotor / Stator	TWISTER D 6-3
Material outflow	DN35 female part
Coupling reduction	DN35 female part DN25 male part
Material hopper	plastic
Castors	2 steering castor, 2 castors
Dimensions: L/W/H	1,600 / 600 / 660 mm
Filling height	610 mm
Weight	~ 133 kg

Kindly note:
All details depends on the used materials.



ADVANTAGES AT A GLANCE



- 1 Low filling height, fits easily under each mixer
- 2 Plastic material hopper - easy cleaning
- Variable conveying output through pump change (D or R pump)
- High conveying capacity and distance
- Universal filling from buckets or continuous mixers
- Handy and compact
- Fast cleaning and maintenance
- Transport is possible in any estate car without dismantling



FIELDS OF APPLICATION

- Adhesive and reinforcement mortar
- Finishing coat
- Insulation mortar
- Floor filler
- Fine filler
- Masonry mortar
- Floor screed up to 60 l/min

ACCESSORIES

- Extension cable 5 x 4 mm², RED 5-32 A - 25 m
- Remote control cable with switch - 25 m
- Protection grille, low required for continuous mixers
- Bag squeezer for SWING L
- Water hose Geka/Geka DN12 - 5 m
- Spray nozzle Geka DN19

PART NO.

- 20 42 39 20
- 20 45 69 29
- 00 25 30 76
- 00 20 15 64
- 20 21 11 00
- 20 21 57 00



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.eu
www.youtube.com/knaufpften

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft-iphofen.de www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT SWING L - GB/01.18/PFT