

PFT ZP 3 M FC-400V

The flexible for great challenges


With a flexible conveying distance and a wide tire size the conveying pump can be almost applicable everywhere on construction sites. Compact, robust and powerful.



TECHNICAL DATA

Part no.	00 54 25 27
Pressure	max. 20 bar
Conveying capacity	continuously adjustable from 8 – 33 litres/min
Conveying distance	up to 60 m
Motor	400 V, 3 Ph, 50 Hz, 4 kW, 120 rpm
Hopper content	85 litres
Spraying gun	DN35 S16 male part Geka
Air compressor	COMP M-250, 400 V, 3 Ph, 50 Hz, 0.9 kW - 250 l/min
Material hose	RONDO DN35 - 10 m
Water/air hose	DN12 Ewo male part Geka - 11 m
Rotor / Stator	RENDER STAR
Material outflow	DN35 female part
Filling height	640 mm
Dimensions: L/W/H	1,800/600/670 mm
Weight	~197 kg

Kindly note:
All details depends on the used materials.



ADVANTAGES AT A GLANCE



- 1** Wide base tyres - good mobility
 - 2** Integrated pressure control for compressor
 - 3** Folded protection grille with switch-off
 - 4** Two handles on the material hopper
 - 5** Handle at the pressure flange
 - 6** Integrated compressor console and hook
 - 7** Optional: Vibrating screen
 - 8** Better cleaning of the machine and the cleaning opening by C-coupling - material hopper runs empty
- Machine shutdown via remote switch
 - Flow - optimized material hopper
 - Frequency converter (FC) for infinitely variable speed control

FIELDS OF APPLICATION

- Job site mixture
- Screed mortar
- Cement plaster

ACCESSORIES / VERSIONS

- Extension cable 5 x 2.5 mm²
RED 5-16 A - 25 m
- Vibrating screen 400 V
- Retrofitting kit for
COMP M-250, 400 V, 3 Ph, 50 Hz
- ZP 3 M FC-230V
- ZP 3 M pole-changing
- ZP 3 M FC-400V

PART NO.

- 20 42 33 60
- 00 53 08 99
- 00 53 52 66
- 00 54 25 26
- 00 54 25 28
- 00 54 25 27



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net
www.youtube.com/knaufpften

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · 97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

PFT ZP 3 M FC-400V - EN/06.19/PFT