

PFT RITMO L FC-230V plus – SD 6-3

The powerful 230 V mixing pump with up to 20 m conveying distance

The proven one-man mixing pump with a SD 6-3 for operation with 230 V alternating current - for the spraying and applying of numerous materials with a grain size up to 3 mm.




TECHNICAL DATA

Part no.	00 65 74 43
Rotor/Stator	SD 6-3 slimline
Conveying capacity	continuously adjustable up to 20 litres / min
Conveying distance	up to 20 m
Material	gypsum plaster
Working pressure	max. 20 bar
Motor	230 V, 1 Ph, 50 Hz, 2.2 kW, 55 – 492 rpm
Connection cable	BLU 3-16 A BLU 2-16 A – 25 m
Spraying gun	DN25-360° S10 200 Ewo
Air compressor	COMP R-80, 230 V, 1 Ph, 50 Hz, 0.35 kW, 80 l / min
Material outflow	DN25 male part
Material hose	RONDO DN25 – 15 + 5 m
Air hose	DN9 Ewo Ewo – 16 + 5 m
Mixing tube	Rubber
Operation	Compressor: pressure control
Hopper content	45 litres
Dimensions: L/W/H	750 / 600 / 1,430 mm
Filling height	930 mm
Weight	~ 133 kg

optional: Rotor/Stator SD 6-3 slimline soft

Conveying capacity	continuously adjustable up to 20 litres / min
Conveying distance	up to 20 m
Material	gypsum plaster, lime-cement plaster
Working pressure	max. 15 bar

Please note:
Standard values depending on mortar quality, mortar composition, mortar consistency, pump version, pump condition, material hose diameter and delivery height. Ultimately, the respective guidelines of the material manufacturer are decisive.



ADVANTAGES AT A GLANCE



- 1** Suitable for bucket and bag material
- 2** Flow-optimized output
- 2** Mortar pressure gauge integrated
- 3** Rubber mixing zone for easy cleaning with adapter flange for A, B and D pump
- 4** Easy dismantlable into single modules
 - Motor with protection grille: 30 kg
 - Material hopper with pump unit: 36 kg
 - Chassis: 64 kg
 - Mixing shaft: 3 kg
- 4** In series equipped with external vibrator
- 5** Flexible mixing intensity thanks to two water inlets
- 6** Easy handling on start-up, retrofitting, maintenance and cleaning
- 6** Foldable motor
- 6** Circumferential sealing edge on the material container for accessories
- 7** Transport is possible in any estate car
- Mounting position for Rotor/Stator mounting
- Conical mixing tube for optimum material flow
- Large insertion area
- Runs powerfully and reliably with luminous flux
- Extension hopper - for double volume

FIELDS OF APPLICATION

- Interior plaster
- Finishing coat
- Floor levelling compound
- Fine filler
- Adhesive / reinforcement mortar
- Fire protection mortar
- Grouting mortar

ACCESSORIES

- Extension cable 3 x 2.5 mm², BLU 2-16 A - 25 m
- Extension hopper for RITMO L plus
- DUSTCATCHER RITMO L plus complete
- Mixing shaft BIONIK RITMO L plus
- Stator SD 6-3 slimline
- Stator SD 6-3 slimline soft
- Rotor SD 6-3 slimline

Further accessories and spare parts could be found at www.pft.net/plus

PART NO.

- 20 42 34 20
- 00 61 27 29



The PFT Service guarantee

Customer-friendliness, technical expertise and service-orientation. That's what the PFT brand with its sales and service centers worldwide stands for also in the coming decades.



Click. Discover. Experience.

www.pft.net/plus
www.youtube.com/knaufpft

Download now! APP: PFT - Plastering Technology

Knauf PFT GmbH & Co. KG

Einersheimer Str. 53 · DE-97346 Iphofen

Technical Hotline +49 9323 31-1818

Phone +49 9323 31-760

Fax +49 9323 31-770

info@pft.net www.pft.net

All rights reserved. Subject to change without prior notice. Our warranty refers only to the perfect condition of our machines. Consumption, quantity, design specifications and performance data are empirical values, which cannot be transferred automatically in case of deviating conditions. In addition, the guidelines of the material manufacturer are always applicable. Changes, reprints and photomechanical reproductions, even in parts, require the approval of Knauf PFT GmbH & Co. KG.

RITMO L plus - SD 6-3 - EN/09.19/PFT