

5.000 m² of surface coating for the newly constructed Police Headquarters in Heidelberg



PFT's machine combo of HM2 and N2V keep things in motion, covering a total area of 5000 m² with the reinforcement mortar, Capatect 133. Plasterers: Meininger GmbH, Kaiserslautern, Germany.

Existing for over a century, Meininger GmbH are specialist painters in Kaiserslautern, Germany. Today the company has a workforce of 30 employees. Among other services, Meininger GmbH's range also extends to the processing of thermal insulation facades.

Rich in traditional skills, Meininger GmbH was given a contract for coating a surface of 5000 m² at the newly constructed Police

Headquarters in Heidelberg. Chief Executive Harald Meininger faced the task of providing the most cost-effective and fastest processing of reinforcement mortar. Manual mortar application was ruled out for reasons of time. State-of-the-art technology was thus called for.

Meininger GmbH received full support through PFT's dealer, Wolfgang Rath, from Siersburg. A machine combination was put

together consisting of PFT's HM2 for pre-mixing, and our new variable pump N2V for spraying the mortar. With a consistent spraying capacity of 26 l/min. the N2V could easily take on mortar hose lengths of 50 m. The mortar consistency that had been adjusted only once at the beginning of machine operation remained constant throughout, right up to the end of the day.

By using our latest machine combo of HM 2 and N2V

for Capatect 133, we were able to keep all deadlines, provide cost-effective solutions and save a lot of time as compared with manual application processes. It might be of interest to you that PFT's new machine combo (mixing, pumping and spraying) can be used for all pumpable mortars, masses and fluids. Machine filling can be done by PFT's Silomat, thus avoiding bagged material.