



PFT ZP3 XL MIX PLASTER MACHINE

Mixing and spraying machine for conventional mortars.

Fields of Application

- Conventional mortar applications

Maintenance, Storage and Handling

- If machines will not be used for a long period of time, by taking out the safety grill, products and wastes in the dry mortar chamber should be cleaned up.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT ZP3 XL MIX	1050	1150	1500	380

Technical Properties

Conveying capacity (L / min)	30
Conveying pressure (bar) max.	max. 20
Conveying distance (m) max.	40
Drive	7,5 kW geared motor, 175 rpm
Power connection	400 V, 3 Ph, Fuse protection: 32 A

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>