



PFT HM 2002 / 2006 MIXING MACHINE

Horizontal screw mixer for all premixed dry gypsum/cement based mortars.

Fields of Application

- Continuously mixing the mortars with grain size up to 4-5 mm

Maintenance, Storage and Handling

- If machines will not be used for a long period of time, by taking out the safety grill, products and wastes in the dry mortar chamber should be cleaned up.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT HM 2002	600	1870	1040	125
PFT HM 2006	650	1650	1000	108

Technical Properties

	HM 2002	HM 2006
Mixing capacity (L / min)	30	25 - 50
Geared motor	2,2 kW	3kW, 280 rpm
Power connection	230 V Alternate current	230 V / 400 V

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>