

## PFT LOTUS XS MIXING MACHINE



**Horizontal screw mixer for especially insulating and tiling mortars.**

### Fields of Application

- Continuously mixing the mortars with grain size up to 4 mm

### Maintenance, Storage and Handling

- If machines will not be used for a long period of time, by taking out the safety grill, products and wastes in the dry mortar chamber should be cleaned up.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

### General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT LOTUS XS	645	1215	880-1200	65

### Technical Properties

Conveying capacity (L / min)	20
Power connection	230 V, 50 Hz, 1 Ph
Drive	1,3 kW geared motor
Speed	280
Water supply	3/4" hose
Hopper content (L)	50

### Ordering Terms

Minimum order quantity is 1 machine.

**For quality certificates visit:** <http://www.knauf.com.tr/kalitebelgeleri.asp>

**For recommended price list visit:** <http://www.knauf.com.tr/fiyatlistesi.asp>