



PFT G4X PLASTER MACHINE

Full automatically and continuously working mixing and pumping machine for ready - mixed dry mortars.

Fields of Application

- Spraying the ready-mixed mortars with grain size up to 0-4 mm.

Maintenance, Storage and Handling

- If machines will not be used for a long period of time, by taking out the safety grill, and the star wheel, products and wastes in the dry mortar chamber should be cleaned up.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT G4X Smart PFT G4X FU 230V/400V	720	1200	1530	292
PFT G4X XL			1650	

Technical Properties

	PFT G4X Smart	PFT G4X FU 230V/400V	PFT G4X XL
Conveying capacity (L / min)	22	22	22
Conveying pressure (bar) max.	30	30	40
Conveying distance (m) for Ø 35 mm	50	50	65
Drive	400 V, 32 Ampere, 3 phase	230/400 V, 32 Ampere, 1/3 phase	400 V, 32 Ampere, 3 phase
Star wheel motor	0.75 kW 28 rpm		
Pump motor	5.5 kW 400 rpm		7.5 kW 400 rpm
Compressor output	D 6-3	D 6-3	D 6-4
Water connection (at running machine)	2,5		
Filling height (mm)	910	910	940

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>