

PFT SWING M TRANSFER PUMP

Small conveying pump for pasty filling plasters.



Fields of Application

- Conveying and applying all pasty materials with grain size up to 3 mm

Maintenance, Storage and Handling

- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT SWING M	460	1100	550	70

Technical Properties

Drive	1.5 kW geared motor
Speed	102 rpm at 50 Hz
Power connection	230 V, 50 Hz, 1 Ph
Fuse protection (Amper)	16
Conveying capacity (L/min)	adjustable btw 0,5 - 9
Conveying distance (m) max.	20
Conveying pressure (bar) max.	20

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>