



PFT SWING L TRANSFER PUMP

Conveying pump with cycle regulated and constant speed options for premixed plasters and mortars.

Fields of Application

- Conveying mortars with grain size up to 5 mm

Maintenance, Storage and Handling

- If machines will not be used for a long period of time, by taking out the safety grill, products and wastes in the dry mortar chamber should be cleaned up.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT SWING L	600	1600	660	130

Technical Properties

Drive	5,5 kW geared motor
Speed	102 rpm at 50 Hz
Power connection	400 V, 50 Hz
Fuse protection (Amper)	16
Conveying capacity (L / min)	adjustable btw 0,6 - 35

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>