



PFT SILOMAT Trans Plus Bag Transfer Pump

Handy, pneumatic conveying equipment of all sort of dry mortars for bag or silo feeding.

Kullanım Alanları

- Spraying all sort of dry mortars to floors with an air support system feeding directly from silos or bags.

Maintenance, Storage and Handling

- If machines will not be used for a long period of time, by taking out the safety grill, products and wastes in the dry mortar chamber should be cleaned up.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
PFT SILOMAT Trans Plus Bag	690	840	980	294

Technical Properties

Conveying capacity (L/min)	20
Conveying distance (m)	140
Conveying pressure (bar) max.	2,5
Power connection	400 V, 50 Hz, 3 Ph
Connection cable	5 x 4mm ² CEE plug
Drive (kW)	8,1
Air capacity (Nm ³ / h)	140
Content (L)	60

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>