

GRACO EH200 SATIN PLASTER AND PAINT SPRAYING MACHINE



Spraying machine for thin plasters, pasty fillers and paints.

Fields of Application

- Finishing (satin) gypsum plaster and paints

Maintenance, Storage and Handling

- If machines will not be used for a long period of time, machinery should be cleaned with thinner.
- Machines and accessories should be cleaned after the long breaks.
- Machine should be settled on a flat and stable surface.
- The signals on the machines and the application guide should be read.
- Original PFT accessories should be used.
- Power connection should be safe and adaptable with the system.
- Machine should be applied by trained persons with using safety glasses and gloves.
- Machine should be switched off during the maintenance and reparation.
- Machine should be maintained by the technical service at least once a year.

General Properties

	Dimension (mm)			Weight (kg)
	Width	Length	Height	
GRACO EH 200	660	1270	920	95

Technical Properties

Power supply	Electric 220 V, single phase
Drive	3,3
Conveying pressure (bar) max.	230
Conveying capacity (L / min)	6
Nozzle	min 0,037" / max 0,041"
Operating pressure (bar) max.	20

Ordering Terms

Minimum order quantity is 1 machine.

For quality certificates visit: <http://www.knauf.com.tr/kalitebelgeleri.asp>

For recommended price list visit: <http://www.knauf.com.tr/fiyatlistesi.asp>