Aquapanel Exterior

Knauf Aquapanel Exterior Tyvek® Water Resistive Barrier

Knauf Aquapanel Exterior Boards and Accessories

Aquapanel Exterior cement board technology sets new standards for the design and construction of buildings across Europe. Aquapanel Exterior offers a high quality and economical alternative to traditional methods of construction, such as brick and block. It provides a solid, dry base that can withstand the extreme weathering effects of wind, rain and snow. It is an ideal substrate for Aquapanel Plaster and other render finishes (subject to approval). It can be used for exterior walls in ventilated systems, water managed (directly applied) systems, exterior ceilings and soffits.

Aquapanel Exterior Tyvek® Water Resistive Barrier is a special climatic membrane to be used as a water barrier from the outside to the inside, while allowing vapour diffusion from the inside to the outside. It is used in water managed (directly applied) systems, installed as a water-carrying layer directly behind the board as part of the Aquapanel Exterior system.

Compliance: EN 13859-2.

| Roll Size | | Material No. | Pallet Details | |
|------------|-----------|--------------|------------------|--------------|
| Length (m) | Width (m) | | Rolls per Pallet | Kg (Approx.) |
| 75 | 1.5 | 438378 | 16 | 0.8 |

Estimating Guide: 1.1m/m².



