



DECLARATION OF PERFORMANCE

No. KAQ_0404

1. Unique identification code of the product-type: **AQUAPANEL® Exterior Mineral Finish - white EMFW_100286_011**
2. Intended use/es: **Rendering mortar CR for internal and external use**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**
Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: aquapanel.info@knauf.com
4. Authorised representative: not applicable
5. System/s of AVCP: **System 4**
6. a) Harmonised standard: **EN 998-1: 2010**
Notified body/ies: **MPA Dresden (0767)**
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body /
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised tech. specification
Reaction to fire	A1	EN 998-1:2010-09
Water absorption	W2	EN 998-1:2010-09
Water vapour diffusion coeff. μ	$\mu \leq 20$	EN 998-1:2010-09
Adhesion	$\geq 0,08 \text{ N/mm}^2$, FP: A, B or C	EN 998-1:2010-09
Thermal conductivity ($\lambda_{10, \text{dry}}$)	$\leq 0,82 \text{ W/(m}\cdot\text{K)}$ for P = 50% $\leq 0,89 \text{ W/(m}\cdot\text{K)}$ for P = 90%	EN 998-1:2010-09
Durability	NPD	EN 998-1:2010-09
Dangerous substances	NPD	EN 998-1:2010-09

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski, General Manager

Iserlohn, 09.06.2016

28.5.2014 L 159/43 Official Journal of the European Union EN

AQUAPANEL®

Be certain, choose AQUAPANEL®