



DECLARATION OF PERFORMANCE

No 0010_Conni_S_2018-07-01

1. Unique identification code of the product-type: EN 15824 – Conni S
2. Intended use/es: On external walls, ceilings, columns and partitions
3. Manufacturer: Knauf Gips KG | Am Bahnhof 7 | D-97346 Iphofen
Tel: +49 (9323) 31-0
Fax: +49 (9323) 31-277
e-mail: zentrale@knauf.de
4. Authorised representative: not relevant
5. System/s of AVCP: System 3 for reaction to fire
System 4 for other characteristics
6. a) Harmonised standard: EN 15824:2017-09
Notified body/ies: MPA Nordrhein-Westfalen (NB 0432) for reaction to fire.
6. b) European Assessment Document: not relevant
European Technical Assessment: not relevant
Technical Assessment Body: not relevant
Notified body/ies: not relevant
7. Declared performance/s:

Essential characteristics	Performance
Reaction to fire	A2-s1,d0
Water vapour permeability	V ₁
Water absorption	W ₃
Adhesion	≥ 0,3 MPa
Durability	NPD
Thermal conductivity	$\lambda_{10,dry,mat} = 0,7 \text{ W/(m} \cdot \text{K)}$
Dangerous substances	NPD
<i>* These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use. Performance declared is for the System of which the product is a part.</i>	

8. Appropriate Technical Documentation
and/or Specific Technical Documentation: not relevant

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Iphofen, 2018-07-01

i. V. Dr. Wolfgang Rümmler
(Head of Research & Development D/CH | Knauf Gips KG)

i. V. Dr. Stephan Dietz
(Head of Product Development Gypsum Plaster | Knauf Gips KG)